



CROSS SECTION

SILT FENCE DETAIL
NOT TO SCALE

PROFILE

MAINTENANCE STANDARDS

- ANY DAMAGE SHALL BE REPAIRED IMMEDIATELY.
- IF CONCENTRATED FLOWS ARE EVIDENT UPWIND OF THE FENCE, THEY MUST BE INTERCEPTED AND CONVEYED TO A SEDIMENT TRAP OR
- IT IS IMPORTANT TO CHECK THE UPWIND SIDE OF THE FENCE FOR SIGNS OF THE FENCE CLOGGING AND ACTING AS A BARRIER TO FLOW AND THEN CAUSING CHANNELIZATION OF FLOWS PARALLEL TO THE FENCE. IF THIS OCCURS, REPLACE THE FENCE OR REMOVE THE TRAPPED SEDIMENT.
- SEDIMENT MUST BE REMOVED WHEN THE SEDIMENT IS 6 INCHES HIGH.
- IF THE FILTER FABRIC (GEOTEXTILE) HAS DEGRADED DUE TO ULTRAVIOLET BREAKDOWN, IT SHALL BE REPLACED.

LAKESIDE INDUSTRIES WILL PERFORM EXCAVATION OF PETROLEUM CONTAMINATED SOIL UNDER THE DIRECT SUPERVISION OF FARALLON CONSULTING. FARALLON WILL PREPARE AN ENVIRONMENTAL MEDIA MANAGEMENT PLAN (EMMP)/CONSTRUCTION MANAGEMENT PLAN (CMP) WHICH WILL INCLUDE SOIL SEGREGATION AND HANDLING TO PREVENT SPREAD OF CONTAMINATION.

RIAN K. HANSEN, PE
PROJECT MANAGER

MARY H. McDOWELL, PLS
PROJECT SURVEYOR

RIAN K. HANSEN, PE
PROJECT ENGINEER

PROJECT LANDSCAPE ARCHITECT
FIRST SUBMITTAL DATE:
SCALE: HORIZ.: 1"=60' VERT.: N/A



8/3/17

STAMP NOT VALID
UNLESS SIGNED AND DATED

JOB NUMBER

LKSD0000-0002

SHEET NUMBER **C2 2**